

146RB Series

MODELS: 146RB-1A-1/146RB-2A-1/146RB-3A-1 146RBL-30-1A/146RBL-30-2A/146RBL-30-3A with 30" arm length

With HORIZONTAL AXIS TRANSVERSE ROTARY HOOK

CONSEW

LARGE BOBBIN WIDE ZIG-ZAG **REVERSE FEED**

SEE REVERSE SIDE FOR MACHINES FEATURING STITCH TYPES 304, 308 LONG ARM AND WETSUIT VERSIONS





by changing gears and cams. (Comes with one set, other sets optional)

SINGLE NEEDLE DROP FEED WALKING FOOT ZIG-ZAG LOCKSTITCH MACHINE 146RBL-30 LONG ARM VERSION Also available for WET SUIT material - (WS) Interchangeable between 1A, 2A, 3A Stitches

146RBL-30 30" Long Arm in 1A, 2A or 3A configuration (special order)

SAG DIN

Models: 1 46RB-1A-1/146RB-2A-1/146RB-3A-1 146RBL-30-1A /146RBL-30-2A /146RBL-30-3A (special order)

APPLICATIONS

146RB-1A-1 – For sewing medium to heavy weight fabrics that are difficult to feed when sewn.

• For such materials and products as wet suits, shoes, boots, leather, tarpaulins. Federal Stitch 304


146RB-2A-1 – Three step/two stitch zig-zag

- For sewing elastic and other stretch materials
- For stitching such products as boat and truck covers, tents, awnings, sails, parachutes, tarpaulins and similar products
- Used on such materials as canvas, nylon, vinyl, leather, synthetics and similar materials.
- Especially desirable where reinforced stitch is necessary. Federal Stitch 308

146RB-3A-1 – Four step/three stitch zig-zag

- Performs similar operations as Model 146RB-2A with the added advantage of making an additional stitch for extra reinforcement.
- **146RBL** Same subclasses as above, but with 30" long arm for 30 inches of workspace.
- \boldsymbol{WS} Wet Suit version available for sewing neoprene rubber





Wide zig-zag

Reverse stitching

FEATURES

- Large bobbin and horizontal axis transverse rotary hook
- Upper feed mechanism helps avoid slippage when sewing
- Stitches per minute 2500*
- Optional: Interchangeable between 1A, 2A & 3A stitches; Additional parts required (not included).

SPECIFICATIONS

Speed, Max. (S.P.M.) *		2500	Hook	B79
Clearance Under Foot		25/64" (10 mm)	Bed Size	Model 146RB-1A-1 7" X 187/8" (178 x 480 mm)
Needle Bar Stroke		1-11/32" (34 mm)		Model 146RBL-30 7" x 331/4" (178 x 848 mm)
Stitch Length, Max.		5 s.p.i. (5 mm)	Work Space	Model 146RB-1A-1 10" (255 mm)
Needle		135 X 17		Model 146RBL-30 30" (765 mm)r
Bobbin	Metal	212034-312	Zig-Zag Stitch	Width, Max. ³ /8" (9.5 mm)
	Pre-wound	М		

* Speed depends on width of zig-zag, material and thread.

Specifications subject to change without notice.



©2007 Consew USA -107