

# MODEL 289 RB-HLP-1

WITH

CENTRA-LUBE® - SEMI-AUTOMATIC LUBRICATION SYSTEM LARGE VERTICAL AXIS ROTARY HOOK AND BOBBIN REVERSE FEED SAFETY CLUTCH





HIGH SPEED
EXTRA HIGH POST TYPE
SINGLE NEEDLE
DROP FEED, NEEDLE FEED
WALKING FOOT
ALTERNATING PRESSER FEET
LOCKSTITCH MACHINE



## Model 289RB-HLP-1

### **APPLICATIONS**

- For sewing medium to heavy weight fabrics, leather, canvas, vinyl, synthetics and various coated and laminated materials
- For stitching uneven, hollow, tubular and curved articles
- Designed for stitching such products as boots, shoes, gloves, luggage, handbags, overalls, raincoats, bags, umbrellas, awnings, covers, tarpaulins, tents, sports and camping equipment, wearing apparel, outdoor clothing, etc.
- Suitable for edge stitching operations

#### FEATURES

- Centra-Lube® semi-automatic lubrication system
- Oil fed take-up
- Extra high post
- Safety clutch prevents the hook from being damaged
- Large bobbin allows for longer operation
- Large vertical axis hook allows for use of thick thread and therefore ornamental stitching can be obtained
- Compound feed, walking foot mechanism assures even feeding of material
- Reverse stitching
- Simple adjustment permits raising and lowering of the center foot which allows for sewing different thicknesses of material

#### **SPECIFICATIONS**

Speed, Max. (S.P.M.) *		2200*	Hook	14119
(* Speed depends on operation, material and thread.)			Bed Size	7" x 20 <sup>3</sup> / <sub>8</sub> " (178 mm x 518 mm)
Clearanc	Hand	<sup>5</sup> /16" (8.5 mm)	Work Surface	2½8" x 2" (54 mm x 51 mm)
	Foot	<sup>5</sup> /8" (16 mm)	Post Height	17- <sup>7</sup> / <sub>16</sub> " (443 mm)
Needle Bar Stroke		1-13/32" (35.3 mm)	Stitch Type	301
Stitch Length, Max.		4 s.p.i. (6.2 mm)	Needle	135 x 17
Bobbin	Metal	15408		
	Pre-wound	S and U		

Specifications subject to change without notice.

©2007 Consew USA -107

