




Since 1898
CONSEW®

Model CN2053R-DD


DIRECT DRIVE / AUTO FUNCTIONS / ZIG-ZAG

WITH

- DIRECT DRIVE BUILT-IN SERVO MOTOR
- VARIABLE SPEED CONTROL
- DIGITAL CONTROLS
- HORIZONTAL AXIS ROTARY HOOK - FRONT LOAD
- REVERSE FEED
- ADJUSTABLE REVERSE STITCH LENGTH
- COMBINATION ZIG-ZAG AND STRAIGHT STITCHER
- NEEDLE POSITION ADJUSTMENT (*Right • Center • Left*)
- NEEDLE POSITION (*Stop-Up / Stop-Down*)
- METAL GEARS (HARDENED STEEL)



Zig Zag Stitching



Federal Stitch 304
One Stitch / Two Steps

SINGLE NEEDLE
DROP FEED
ZIG-ZAG
LOCKSTITCH MACHINE
Direct Drive

(Servo Motor connected to Top Shaft)

Models CN2053R-DD

APPLICATIONS

- For sewing light to medium heavy weight fabrics including clothing, shoes and caps, leather articles, bags and more
- For attaching lace, elastic band, bottom hemming, edge stitching, butted seaming, applique and similar operations
- Federal stitch type 304
- CN2053R-2A has Stitch type 308 (*used to secure lines on parachutes*)
- CN2253R-1A for piping and cording. Top of material will show a double-needle 5 mm stitch, and bottom of material will show a zig-zag stitch



FEATURES

- Automatic Foot Lift
- Automatic Reverse
- Convenient push-button digital control switches
- Horizontal axis transverse rotary hook - Front Load
- Dial stitch regulator
- Locking zig-zag width regulator lever
- Straight stitches when zig-zag set to "0" and has straight stitch locking device
- Stitches per minute — up to 1800*
- Reverse stitching with adjustable stitch length
- Needle Position Adjustment (*right • center • left*)
- Needle Position (*Stop-Up / Stop-Down*)
- Built-in free-hand monogramming lever
- Direct Drive Built-in Servo Motor
- Variable Speed Control
- Metal gears (hardened steel)

SPECIFICATIONS

CN2053R-DD

Speed, Max. (S.P.M.) *	1800	
Clearance Under Foot	by hand	15/64" (6 mm)
	by knee	25/64" (10 mm)
Needle Bar Stroke	1 6/25" (31.5 mm)	
Stitch Length, Max.	5 s.p.i. (5 mm)	
Needle	135 x 5	
Bed Size	7" x 15 11/16" (178 x 398.5 mm)	
Work Space	8 5/16" (211 mm)	
Stitch Width Max.	11/32" (9 mm)	
Stitch Type	304 (or Straight 301)	
Power	110 vac	



Closeup of needle



Also available is the traditional CN2053R-1A NON-direct drive machine

* Speed depends on width of zig-zag, material and thread.

Specifications subject to change without notice.

©2022 Consew USA -0422