24



WITH STAINLESS STEEL BED PLATE AUTOMATIC LUBRICATION REVERSE FEED JAPANESE COMPONENTS



# ULTRA HIGH SPEED SINGLE NEEDLE DROP FEED LOCKSTITCH MACHINE



# Model 7360R-2SS

## APPLICATIONS

- For sewing light to heavy-weight materials including cottons, knits, polyester, nylon, sheer fabrics and denim
- Suitable for stitching such products as blouses, shirts, men's, ladies and children's apparel, uniforms, overalls, lingerie, etc.
- Heavyweight fabrics such as jeans can be sewn by changing the needle plate, feed dog, foot, stitch regulator, hook and needle bar

### FEATURES

• Stainless steel bed plate. This separates Consew from other brands. It costs more to produce and besides looking really hi-tech, is longest lasting surface you can find.

Advantages of a Stainless Steel Bed Plate:

- Preserves the appearance of the bed No paint to get worn off Therefore enhancing resale value.
- Resists rust.
- Lets the fabric move more easily (less friction) thus improving efficiency.
- Non-Magnetic Can be easier when sewing magnetic tape, grommets and snaps.
- Fully automatic lubrication with recirculating high pressure pump
- Noise and vibration absorbing table mounting
- "Feather-touch" pressure foot lifter
- Ultra high speed 5500 S.P.M.\* (see below)

### SPECIFICATIONS

Model 7360R-2SS   Speed,@ Max. (S.P.M.) * 5500*   Clearance Under Foot 1/4" (6 mm)   Needle Bar Stroke 1 1/4" (31.8 mm)   Stitch Length, Max. 5 SPI (5 mm)   Needle 16 x 257   Bobbin Metal 22T4-017   Pre-wound L   Hook 22T4-011D   Bed Size 7" x 18 <sup>7</sup> /8" (177 x 477 mm)   Work Space 10" (258 mm)   Stitch Type 301			
Clearance Under Foot 1/4" (6 mm)   Needle Bar Stroke 1 1/4" (31.8 mm)   Stitch Length, Max. 5 SPI (5 mm)   Needle 16 x 257   Bobbin Metal 22T4-017   Pre-wound L   Hook 22T4-011D   Bed Size 7" x 18 <sup>7</sup> /8" (177 x 477 mm)   Work Space 10" (258 mm)	Model		7360R-2SS
Needle Bar Stroke 1 1/4" (31.8 mm)   Stitch Length, Max. 5 SPI (5 mm)   Needle 16 x 257   Bobbin Metal 22T4-017   Pre-wound L   Hook 22T4-011D   Bed Size 7" x 18 <sup>7</sup> /8" (177 x 477 mm)   Work Space 10" (258 mm)	Speed,@ Max. (S.P.M.		* 5500*
Needle 16 x 257   Bobbin Metal 22T4-017   Hook 22T4-011D   Bed Size 7" x 18 <sup>7</sup> /8" (177 x 477 mm)   Work Space 10" (258 mm)	Clearance Under Foot		1/4" (6 mm)
Needle 16 x 257   Bobbin Metal 22T4-017   Pre-wound L   Hook 22T4-011D   Bed Size 7" x 18 <sup>7</sup> /8" (177 x 477 mm)   Work Space 10" (258 mm)	Needle Bar Stroke		1 1/ <sub>4</sub> " (31.8 mm)
Bobbin Metal 22T4-017   Pre-wound L   Hook 22T4-011D   Bed Size 7" x 18 <sup>7</sup> /8" (177 x 477 mm)   Work Space 10" (258 mm)	Stitch Length, Max.		5 SPI (5 mm)
Bobbin Pre-wound L   Hook 22T4-011D   Bed Size 7" x 18 <sup>7</sup> /8" (177 x 477 mm)   Work Space 10" (258 mm)	Needle		16 x 257
Pre-wound L   Hook 22T4-011D   Bed Size 7" x 18 <sup>7</sup> /8" (177 x 477 mm)   Work Space 10" (258 mm)	Bobbin	Metal	22T4-017
Bed Size 7" x 18 <sup>7</sup> /8" (177 x 477 mm)   Work Space 10" (258 mm)		Pre-wound	L
Work Space 10" (258 mm)	Hook		22T4-011D
	Bed Size		7" x 18 <sup>7</sup> / <sub>8</sub> " (177 x 477 mm)
Stitch Type 301	Work Space		10" (258 mm)
	Stitch Type		301



\* Speed depends on materials, thread and operation