

DOUBLE NEEDLE

MODELS 339RB-4 / 339RBL-25

WITH CENTRA-LUBE®

SEMI-AUTOMATIC LUBRICATION SYSTEM

LARGE VERTICAL AXIS HOOKS AND BOBBINS

2½ S.P.I.(10mm) STITCH LENGTH







HEAVY DUTY HIGH SPEED TWO NEEDLE

LOCKSTITCH MACHINE DROP FEED, NEEDLE FEED and ALTERNATING (WALKING) PRESSER FEET



Models 339RB-4 / 339RBL-25

APPLICATIONS

- For sewing light to heavy-weight materials such as leather, vinyl, upholstery, synthetics, canvas, vinyl and various coated and laminated products
- Designed for stitching such products as auto, boat and furniture upholstery, tarpaulins, covers, sails, tents, camping trailer covers, awnings, umbrellas, tops, bags, luggage, handbags, travelware accessories, sports and camping equipment, wearing apparel, outdoor clothing, canvas shoes, slippers, orthopedic appliances, etc.
- Suitable for double needle seaming, binding, taping and piping operations

FEATURES

- Two needle mechanism readily makes two parallel lines of stitches
- · Compound feed, walking foot mechanism insures even feeding of material
- Large hooks and bobbins assures longer operation between bobbin changes
- Centra-Lube® semi-automatic lubrication system
- Automatic hook lubrication
- · Oil fed take-up
- Simple adjustment permits raising and lowering of the center foot which allows for sewing different thicknesses of material
- Safety clutch protects the hooks from being damaged
- Various needle gauges available
- Synchronized puller available (add suffix -P)



339RBL-25 - Large hooks and bobbins, reverse feed and LONG ARM/Long Stitch - 2½ S.P.I.

339RBL-USA - Special order, custom made in USA, up to 30" LONG ARM

SPECIFICATIONS

Speed, Max. (S.P.M.) *339RB-4 339RBL-25		3000 2400
Clearance Under Foot		⁹ / ₁₆ " (14mm)
Needle Bar Stroke		1-5/ ₁₆ " (33 mm)
Stitch Length, Max.	339RB-4	2½ s.p.i. (10 mm)
	339RBL-25	2½ s.p.i. (10 mm)
Needle		135 x 17
	Metal	15041
Bobbin	Pre-wound	S or U

Hook		15502
Bed Size	339RB-3 339RBL-25	7" x 20- ³ /8" (177 x 518 mm) 7" x 28- ¹ /4" (177 x 718 mm)
Work Space	339RB-3 339RBL-25	10" (258mm) 25" (640 mm)
Standard Needle Spacing		1/4" (6.4 mm)
Available Needle Spacings		¹ / ₈ " (3.2mm) – 1- ¹ / ₂ " (38.1mm)
Stitch Type		301
* Speed depends on operation, material and thread		

Specifications subject to change without notice.

©2007 Consew USA -107



