

NEW TECH GC-1900A STITCH GUILD

This machine is applicable to sewing bar tacks on garment's strained sections. The servo motor directly installed on the main shaft. By operation panel, you can select required sewing speed, sewing patterns and enlarge or reduce seam size. Special patterns are also can be realized such as umbrella circula tack and suit's decorative bott-onhole. It's the best choice for manufacturing various kings of garments in small batches.



Accordance with the customer's different requirement, it can program the special design for garment factory

NO	[Stitch Diagram]	(mm)			NO	[Stitch Diagram]	(mm)			NO	[Stitch Diagram]	(mm)		
1	[Stitch Diagram]	42	16	2.0	18	[Stitch Diagram]	28	10	0.0	35	[Stitch Diagram]	130	9	9.0
2	[Stitch Diagram]	39	10	2.0	19	[Stitch Diagram]	28	25	0.0	36	[Stitch Diagram]	140	9	9.0
3	[Stitch Diagram]	42	16	2.5	20	[Stitch Diagram]	36	25	0.0	37	[Stitch Diagram]	150	9	9.0
4	[Stitch Diagram]	42	24	3.0	21	[Stitch Diagram]	41	25	0.0	38	[Stitch Diagram]	42	10	7.0
5	[Stitch Diagram]	27	10	2.0	22	[Stitch Diagram]	44	25	0.0	39	[Stitch Diagram]	57	10	7.0
6	[Stitch Diagram]	30	16	2.5	23	[Stitch Diagram]	27	4.0	20.0	40	[Stitch Diagram]	102	19	2.6
7	[Stitch Diagram]	35	10	2.0	24	[Stitch Diagram]	35	4.0	20.0	41	[Stitch Diagram]	120	20	3.6
8	[Stitch Diagram]	38	16	2.5	25	[Stitch Diagram]	41	4.0	20.0	42	[Stitch Diagram]	101	19	3.0
9	[Stitch Diagram]	53	24	3.0	26	[Stitch Diagram]	56	4.0	20.0	43	[Stitch Diagram]	141	40	20.0
10	[Stitch Diagram]	61	24	3.0	27	[Stitch Diagram]	18	0	20.0	44	[Stitch Diagram]	81	20	20.0
11	[Stitch Diagram]	20	6	2.5	28	[Stitch Diagram]	21	0	10.0	45	[Stitch Diagram]	42	20	20.0
12	[Stitch Diagram]	25	6	2.5	29	[Stitch Diagram]	21	0	20.0	46	[Stitch Diagram]	48	24	20.0
13	[Stitch Diagram]	34	6	2.5	30	[Stitch Diagram]	28	0	20.0	47	[Stitch Diagram]	62	24	18.0
14	[Stitch Diagram]	15	8	2.0	31	[Stitch Diagram]	90	9	9.0	48	[Stitch Diagram]	220	20	20.0
15	[Stitch Diagram]	22	8	2.0	32	[Stitch Diagram]	100	9	9.0	49	[Stitch Diagram]	42	9	9.0
16	[Stitch Diagram]	29	8	2.0	33	[Stitch Diagram]	110	9	9.0					
17	[Stitch Diagram]	21	10	0.0	34	[Stitch Diagram]	120	9	9.0					

Main specifications

[Icon]	[Icon]	[Icon]	[Icon]	[Icon]	[Icon]	[Icon]	[Icon]	[Icon]	[Icon]
-K1900ASS	DP×5(14#)	★	★	★	★	17	2700	825×403×600	55/50
-K1900AHS	DP×17(19#)	★	★	★	★	17	2700	825×403×600	55/50
-K1900AFS	DP×5(11#)	★	★	★	★	17	2700	825×403×600	55/50
-K1900AMS	DP×5(11#)	★	★	★	★	17	2700	825×403×600	55/50