


MODELS 29/29B/29L/29BL

With

Oscillating Shuttle

Extra Small Cylinder Bed

Universal Upper Feed



SINGLE NEEDLE 12" or 18" CYLINDER ARM SHOE REPAIR AND MENDING LOCKSTITCH MACHINE



Model 29/29B/29L/29BL

APPLICATIONS

Repairing of leather materials and shoe uppers.

FEATURES

- Extra small cylinder bed.
- Oscillating Shuttle
- Universal upper feed for stitching in any direction without turning work
- Handwheel can be mounted on front or right end of machine.
- Wheel pulley "V" groove for motor drive.
- Double ended needle plate with different size holes at back end to accommodate various size needles.
- Adjustable thread take-up lever.
- Adjustable presser foot pressure and thread tension.
- Machine can be driven by foot treadle, hand crank or electric motor.
- Available in regular and large bobbin (B) versions
- Available in regular and long arm (L) versions





All 29's can have the hand wheel mounted on the **end**, as above, or on the **front**, as in the photos on the first page.

SPECIFICATIONS

	Model 29	Model 29B	Model 29L	Model 29BL
Speed, Max. (S.P.M.) *	500	500	500	500
Clearance Under Presser Foot	13/ ₃₂ s.p.i. (10.5mm)	13/ ₃₂ s.p.i. (10.5mm)	13/ ₃₂ s.p.i. (10.5mm)	13/ ₃₂ s.p.i. (10.5mm)
Stitch Length	3.5 s.p.i. (1-7mm)	3.5 s.p.i. (1-7mm)	3.5 s.p.i. (1-7mm)	3.5 s.p.i. (1-7mm)
Hook Size	Small	Large	Small	Large
Work Space	12" (310mm)	12" (310mm)	18" (460mm)	18" (460mm)
Width of Cylinder Bed	1" (25.4mm)	1 ⁵ / ₃₂ " (27.8mm)	1" (25.4mm)	1 ⁵ / ₃₂ " (27.8mm)
Depth of Cylinder Bed	⁷ /8" (22.2mm)	1 ³ / ₃₂ " (29.4mm)	⁷ / ₈ " (22.2mm)	1 ³ / ₃₂ " (29.4mm)
Needle	29x3, Style 3741	29x3, Style 3741	29x3, Style 3741	29x3, Style 3741
Net Weight	62 lbs. (28kgs)	62 lbs. (28kgs)	77 lbs. (35kgs)	77 lbs. (35kgs)
Gross Weight	70.5 lbs. (32kgs)	70.5 lbs. (32kgs)	88 lbs. (40kgs)	88 lbs. (40kgs)
Total Carton Size	3.2 ft ³ (.09cbm)	3.2 ft ³ (.09cbm)	5.3 ft ³ (.15cbm)	5.3 ft3 (.15cbm)

^{*} Depending on materials and thread